



# FormulaShell® 5W-20 Conventional Motor Oil

## Conventional Motor Oil

Meets API Service Categories SN, SM, SL etc. and Resource Conserving ILSAC GF-5 specifications.

Has enhanced wear protection and outstanding resistance to thermal breakdown at operating temperatures.

### DESIGNED TO MEET CHALLENGES

#### Performance, Features & Benefits

FORMULASHELL® CONVENTIONAL MOTOR OIL meets or exceeds the North American warranty requirements for U.S., European and Japanese cars and light trucks with gasoline and gasoline turbo-charged engines where API SN with Resource Conserving, SN, SM, SL, SJ etc. oils are specified. Benefits are as follows:

- Protection for extremely high temperatures.
- Protection against harmful deposits and acids, which aids in a clean running and lasting engine.
- May be used at any time in an engines life-cycle and is fully compatible with conventional engine oils.

#### Main Applications

FORMULASHELL® CONVENTIONAL MOTOR OIL is formulated for improved fuel economy and to provide engine protection and performance required by modern engines.

FORMULASHELL® CONVENTIONAL MOTOR OIL is compatible with other conventional and synthetic oils. It exceeds all automobile and light truck warranty requirements for gasoline and turbocharged engines where an API SN and ILSAC GF-5 oil is recommended.

#### Specifications, Approvals & Recommendations

- GM 6094M
- Chrysler MS-6395
- Ford WSS-M2C945-A and WSS-M2C930-A

Exceeds the requirements of the following industry specifications:

- API SN and all previous categories
- ILSAC GF-5

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk.

Always follow manufacturer's recommendations and specifications for viscosity grade and API service.

#### Typical Physical Characteristics

Properties		Method	FormulaShell® Conventional Motor Oil
SAE Viscosity Grade			5W-20
API Service Category			SN
ILSAC			GF-5
Density	kg/m <sup>3</sup>	ASTM D4052	855
Flash Point	°C	ASTM D93	227
Pour Point	°C	ASTM D97	-42
Viscosity	@40°C mm <sup>2</sup> /s	ASTM D445	50.2
Viscosity	@100°C mm <sup>2</sup> /s	ASTM D445	8.6
Viscosity Index		ASTM D2270	151
CCS Viscosity	@-30°C cP	ASTM D5293	5,140
MRV Viscosity	@-35°C cP	ASTM D4684	15,000

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

## Health, Safety & Environment

- **Health and Safety**

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

- **Protect the Environment**

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

## Additional Information

- **Advice**

Advice on applications not covered here may be obtained from your Shell representative.