



Product Bulletin

GULF SYNTHETIC HYPOID GEAR LUBRICANTS

Gulf Synthetic Hypoid Gear Lubricants are synthetic, heavy duty, extreme pressure, gear and bearing lubricants designed for use in limited slip and conventional differentials, manual transmission, transfer cases of cars, trucks, farm equipment and construction equipment. They are formulated using synthetic base stock, which has very high viscosity index and exceptionally low pour point. The high and low temperature performance of these products exceeds those of conventional SAE 80W-90 and SAE 85W-140 hypoid gear lubricants and offers exceptional protection over a wide range of operating temperatures.

FEATURES AND BENEFITS:

These lubricants contain extreme pressure additives, as well as rust, oxidation, and corrosion inhibitors to protect gears and bearings operating under a wide variety of load conditions. These products promote longer gear life and better operating economy. **Gulf Synthetic Hypoid Gear Lubricants** offer the following advantages over conventional mineral-based gear fluids:

- Extended drains; with manufacturers recommendation, highly oxidation resistance
- Suitable for use in limited slip differentials
- Superior low-temperature performance and all season lubrication
- Improved fuel mileage, result of synthetic stock rheology
- Excellent demulsibility-separates water readily and shear stability
- Non-foaming

Gulf Synthetic Hypoid Gear Lubricants are recommended for applications where heat and wear present major problems. These applications include manual transmissions where hypoid type lubricants are recommended, differentials including limited slip, and transfer cases for heavy equipment, trucks, tractors, and industrial gear drives. These synthetic gear oils provide performance features that make them suitable for use in the following:

- API Service Classification GL-5 and MT-1
- SAE J2360; former U.S. Military Specification MIL-PRF-2105E
- Mack GO-J (all grades)
- Eaton Axle Division PS-037, PS-163, PS-109 (75W-90)
- Dana SHAES-256 rev.C, SHAES-234
- Meritor Automotive 0-76 E/N (75W-90), 0-76B, 0-80 (80W140)

08/16

NU-TIER BRANDS, INC.

UNDER LICENSE FROM GULF OIL LP • TULSA, OK 74133 • Phone 918-550-8026 • www.gulflubricants.net or www.Nu-Tierbrands.com

SELECTION:

Gulf Synthetic Hypoid Gear Lubricants are available in three viscosity grades, SAE 75W-90, SAE 75W-140, and SAE 80W-140 as noted in the chart below. Follow equipment manufacturer recommendations for appropriate viscosity grades.

AVAILABILITY:

Gulf Synthetic Hypoid Gear Lubricants are available throughout Gulf's marketing area. Your Gulf representative can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853) or visit Nu-tierbrands.com.

Typical Properties

SAE Grade	Test Method	75W-90	75W-140	80W-140
Product Code		337201	337203	337202
Viscosity, cSt @ 40°C	ASTM D-445	110.8	180.2	219.8
Viscosity, cSt @ 100°C	ASTM D-445	15.8	25.0	27.3
Brookfield cP at Temp	ASTM D-2983	110,000@-40°C	135,000@-40°C	75,000@-26°C
Viscosity Index		152	172	160
Channel Point, °C		<-45.0	<-45.0	NR
Foam Test	ASTM D-892	Pass	Pass	Pass
Copper Corrosion	ASTM D-130	Pass	Pass	Pass
Thermal Heat Test, 149°C		Pass	Pass	Pass
Demulsibility	ASTM D-1401	Pass	Pass	Pass
Timken OK Load		50	85	85
FZG Scuffing Test, stages	ASTM D-5182	12	12	12
API Service		GL-5/MT-1	GL-5/MT-1	GL-5/MT-1
Pour Point	ASTM D-97	-45°F	-36°F	-30°F