



PRODUCT DATA SHEET

Oilzum Synthetic Multi-Grade Motor Oil

Oilzum Synthetic Motor Oils are designed to exceed the demanding lubrication requirements of today's naturally aspirated, turbo-charged and super charged gasoline engines. Specially formulated with 100% synthetic base oils in combination with leading-edge additive technology, they deliver exceptional resistance to thermal breakdown, oil thickening and low temperature fluidity. They provide superior protection against wear and deposit formation under the most severe driving conditions.

Oilzum Synthetic Motor Oils are specially formulated to exceed the American Petroleum Institute's (API) latest performance Gasoline Engine Service category SN Plus. These viscosity grades are classified by the API as "Energy Conserving" engine lubricants, and meet ILSAC GF-6A. These viscosity grades are also recommended for the requirements of previous categories SM,

TYPICAL PROPERTIES	0W-16	0W-20	5W-20	5W-30
Viscosity @40°C, cSt	38.00	45.00	46.80	57.10
Viscosity @100°C, cSt	7.50	8.7	8.50	10.10
Viscosity Index	169	176	160	166
Pour Point, °C	-52	-51	-50	-48
Zinc, wt. %	0.0780	0.0740	0.0740	0.0740
Phosphorus, wt. %	0.0700	0.0600	0.0600	0.0600
Calcium, wt. %	0.1290	0.1270	0.1260	0.1260
Specific Gravity	0.8444	0.8454	0.8454	0.8467
HTHS	2.4	2.7	2.7	3.10
API Service performance	SN Plus	SN Plus	SN Plus	SN Plus
ILSAC GF-6A	Yes (GF6B)	Yes	Yes	Yes
Energy Conserving	Yes	Yes	Yes	Yes



Oilzum products have exceeded the needs of auto enthusiasts and champion racers since 1905!

DENNISON LUBRICANTS, INC. 102 CHARLES A. ELDRIDGE DRIVE, LAKEVILLE MA, 02347

All reasonable care has been taken to ensure that the information herein is accurate as of the date of printing. The test results listed are typical properties only. DENNISON LUBRICANTS, INC. strives for continuing improvement in all of our products. Slight formula and blending changes may result in minor color and/or appearance changes.