



Outstanding Quality Products  
Competitive Prices  
Superior Service

## Series MILES MIL-GEAR S

### Synthetic EP Gear Lubricant

Series **MILES MIL-GEAR S** is designed for heavy-load and high-temperature applications and formulated with enhanced extreme-pressure (EP) additives. Series MILES MIL-GEAR S provides excellent protection and long fluid life — even in the most demanding applications and environments.

### ATTRIBUTES

- Excellent lubricity
- Very high film strength
- Outstanding carbon and varnish control
- Excellent fluid life
- Excellent dispersant properties
- Enhanced resistance against water contamination
- Excellent protection against wear, rust and corrosion
- Reduced maintenance costs and downtime
- Non-toxic/non-hazardous

### TYPICAL PROPERTIES

Lubrication Properties	MILES MIL-GEAR S 75w90	MILES MIL-GEAR S 80w140
Viscosity Index	142	173
Vis cSt @ 40 °C	110	260.0
Vis cSt @ 100°	15.0	33.2
Flash Point °F	510	515
Auto-Ignition Point °F	839	839
Pour Point °F	-40	-35
Timken "OK" Load Lb.	50	40
Copper Corrosion, 24 Hr.	1b	1b
Sealed Tube Stability	40/38/2	40/38/2