



Outstanding Quality Products
Competitive Prices
Superior Service

MILES SB COMP OIL PLUS

Synthetic Blend Plus Air Compressor Lubricant

Series **MILES SB COMP OIL PLUS** Synthetic Blend Plus Compressor Lubricants are premium fluids blended from the finest materials available. They have been proven in millions of horsepower hours. Series MILES SB COMP OIL PLUS compressor lubricants give outstanding service—even in moderately severe operating conditions.

ATTRIBUTES

- Long fluid life with enhanced thermal and oxidative stability
- Excellent protection against wear, rust and corrosion
- Reduced maintenance costs and downtime
- Excellent resistance against water contamination
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

Lubrication Properties	MILES SB COMP OIL PLUS-32	MILES SB COMP OIL PLUS-46	MILES SB COMP OIL PLUS-68	MILES SB COMP OIL PLUS-100	MILES SB COMP OIL PLUS-150
Viscosity cSt @ 0°C	292	472.6	830	1539	2276
Viscosity cSt @ 40°C	33.2	48.0	68.4	100.1	150
Viscosity cSt @ 80°C	9.3	12.6	16.1	24.0	30.1
Viscosity cSt @ 90°C	7.4	7.8	12.3	15.5	22.4
Viscosity cSt @ 100°C	6.0	7.9	9.7	12.0	17.1
Flash Point °F	420	440	453	465	517
Auto-Ignition Point °F	741	767	703	786	839
Pour Point °F	-35	-30	-29	-29	-15
Four Ball, 40 Kg, 1200 RPM, 167°F, 1 hr, Scar Dia mm	.45	.45	.45	.44	.40
Four Ball Weld Point, Kg	100	100	100	100	100
Copper Corrosion, 24 Hr	1a	1a	1a	1a	1a
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0	40/40/0