



Outstanding Quality Products
Competitive Prices
Superior Service

MILES SB GAS COMP

Synthetic Blend Gas Compressor Lubricant

MILES SB GAS COMP is a gas compressor lubricant formulated to provide long oil life in demanding applications and environments. This exceptional formulation utilizes a blend of synthetic base fluids and advanced additives to provide protection against thermal and oxidative breakdown as well as superior protection against wear, corrosion and rust.

ATTRIBUTES

- Controls carbon and varnish formation
- Formulated to resist washout
- Long oil life
- Resists water contamination
- Protects against wear, rust and corrosion
- Saves energy
- High flash point
- Non-toxic/non-hazardous
-

TYPICAL PROPERTIES

Lubrication Properties	SB GAS COMP-68	SB GAS COMP-100	SB GAS COMP-150	SB GAS COMP-220
Viscosity cSt @ 40°C	68	98	152	201
Viscosity cSt @ 100°C	8.8	11.3	15.4	18.7
Viscosity Index	102	101	103	104
Flash Point °F (°C)	438 (225)	446 (230)	451 (232)	448 (231)
Pour Point °F (°C)	-40 (-40)	-35 (-37)	-33 (-28)	-23 (-30)
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 130°F, 30 Min	40/40/0	40/38/2	40/38/2	40/38/0