

MILES SIL COMP OIL

Silicone Compressor Lubricant

MILES SIL COMP OIL is a premium silicone compressor fluid designed specifically to replace OEM silicone fluids. Completely compatible with virtually all OEM silicone compressor fluids, MILES SIL COMP OIL can be mixed in any ratio and provide the same outstanding fluid life. It is formulated with an advanced-technology additive system for superior performance and also protects against oxidation, wear, rust and corrosion.

ATTRIBUTES

- Top-off compatible with virtually all OEM silicone compressor fluids
- Incredibly long fluid life
- Enhanced wear protection
- Excellent carbon and varnish control
- Outstanding oxidative stability
- Enhanced rust and corrosion protection
- Excellent film strength
- Very high flash point
- Reduced maintenance costs and downtime

TYPICAL PROPERTIES

Lubrication Properties	MILES SIL COMP OIL
Viscosity cSt @ 0°C	91.7
Viscosity cSt @ 40°C	39.21
Viscosity cSt @ 80°C	21.0
Viscosity cSt @ 90°C	18.4
Viscosity cSt @ 100°C	16.25
Flash Point °F	575
Auto-Ignition Point °F	805
Pour Point °F	-67
Four Ball, 40 Kg, 1200 RPM, 167°F, 1 Hr, Scar Dia mm	1.99
Four Ball Weld Point, Kg	126
Copper Corrosion, 24 Hr	1a
Demulsibility, 130 °F, 30 Min	40/40/0