

## Outstanding Quality Products Competitive Prices Superior Service

## MILES SXR COMP COOLANT

Full Synthetic Compressor Coolant

MILES SXR COMP COOLANT offers full compatibility with most OEM polyalkylene glycol (PAG) compressor lubricants. This compatibility means that flushing of the existing compressor oil is not necessary to change to MILES SXR COMP COOLAN, reducing maintenance costs and downtime. MILES SXR COMP COOLANT offers superb resistance against water contamination and an extended service life of 8,000 hours.

## **ATTRIBUTES**

- 8,000-hour oil life at 100°C discharge temperature
- Compatible with most OEM PAG compressor lubricants
- Resists water contamination
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

## TYPICAL PROPERTIES

| MILES SXR COMP COOLANT     | 32        | 46        | 68      |
|----------------------------|-----------|-----------|---------|
| Viscosity cP @ 0°C         | 344       | 699       | 936     |
| Viscosity cSt @ 40°C       | 32        | 46.1      | 68      |
| Viscosity cSt @ 60°C       | 15.15     | 19.9      | 29.3    |
| Viscosity cSt @ 80°C       | 8.53      | 10.5      | 15.2    |
| Viscosity cSt @ 100°C      | 5.42      | 6.6       | 9.1     |
| Flash Point °F (°C)        | 435 (224) | 465 (241) | 460     |
| Copper Corrosion, 24 Hr    | 1a        | 1a        | 1a      |
| Rust Test: Distilled Water | Pass      | Pass      | Pass    |
| Rust Test: Salt Water      | Pass      | Pass      | Pass    |
| Foam Sequence I, II, III   | 0/0/0     | 0/0/0     | 40/40/0 |