



Outstanding Quality Products
Competitive Prices
Superior Service

MILES SXR COMP OIL

Advanced-Technology Synthetic Air Compressor Lubricant

MILES SXR COMP OIL utilizes the latest high-performance, full-synthetic base stocks and additives. This formulation offers an exceptional level of protection against wear, rust and corrosion, as well as outstanding resistance against oxidation and thermal breakdown.

MILES SXR COMP OIL is designed to provide 8,000+ hours of service.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Excellent thermal stability
- Resists water contamination
- Saves energy
- High flash point
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL PROPERTIES

MILES SXR COMP OIL 100 Viscosities	32	46	68	100
Viscosity cP @ 0°C	311	617	917	1692
Viscosity cSt @ 40°C	30.4	45	64	105
Viscosity cSt @ 60°C	14.6	19.9	27.47	42.82
Viscosity cSt @ 80°C	8.3	10.6	14.32	21.37
Viscosity cSt @ 100°C	5.3	6.5	8.57	12.33
Flash Point °F (°C)	430 (221)	445 (229)	451 (233)	503 (262)
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0