



Outstanding Quality Products  
Competitive Prices  
Superior Service

## MILES UNIV COMP OIL Universal Air Compressor Lubricant

MILES UNIV COMP OIL is formulated to provide complete compatibility with a wide variety of OEM and aftermarket rotary screw compressor lubricants. Flushing is not required to switch to MILES UNIV COMP OIL; in most cases, it can be added directly on top of the existing compressor oil. Its advanced formulation helps avoid costly lubricant-contamination mistakes and helps streamline product inventory. MILES UNIV COMP OIL is also formulated to provide outstanding resistance against wear, rust, corrosion and sludge buildup, and to provide 8,000+ hours of service.

Top-off compatible with:

- PAG-based compressor lubricants
- POE-based compressor lubricants
- Diester-based compressor lubricants
- PAO-based compressor lubricants
- Partial-, semi- and petroleum-based compressor lubricants

### ATTRIBUTES

- Universal formulation, compatible with most OEM and aftermarket rotary screw air compressor lubricants
- 8,000+ hours of oil life at 100°C discharge temperature
- Oxidatively and thermally stable
- High flash point
- Controls carbon and varnish formation
- Low volatility
- Excellent film strength
- Non-toxic/non-hazardous

### TYPICAL PROPERTIES

Lubrication Properties	UNIV COMP OIL
Viscosity cSt @ 40°C	46
Viscosity cSt @ 100°C	7.7
Viscosity Index	135
Flash Point °F (°C)	468 (242)
Auto-Ignition Point °F (°C)	725 (385)
Pour Point °F (°C)	-34 (-37)
Copper Corrosion, 24 Hr	1a
Demulsibility, 130°F, 30 Min	40/39/1