

## MILES SXR GAS COMP Synthetic Gas Compressor Lubricant

Designed specifically for natural gas compressors, **MILES SXR GAS COMP** is formulated using an advanced-technology blend of synthetic base fluids and additives. It offers enhanced resistance against oxidation as well as carbon formation, rust and corrosion.

### ATTRIBUTES

- Designed for use with the compression of natural gas or natural gas containing carbon dioxide or hydrogen sulfide
- Formulated to resist washout
- Long oil life
- Resists water contamination
- Protects against wear, rust and corrosion
- Saves energy
- High flash point
- Non-toxic/non-hazardous

### TYPICAL PROPERTIE

MILES SXR GAS COMP ISO 68 Viscosities	100	150	220	320
Viscosity cSt @ 40°C	104	150	219	320
Viscosity cSt @ 100°C	12.8	16.8	23.7	30.8
Viscosity Index	118	120	134	133
Flash Point °F (°C)	502 (261)	505 (263)	507 (264)	508(264)
Pour Point °F (°C)	-54 (-48)	-52 (-47)	-50 (-46)	-48(-44)
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Demulsibility, 54°C, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0